Section 8: Execution control

The execution sequence may be controlled by constructs containing blocks and by certain executable statements that are used to alter the execution sequence.

8.1 Executable constructs containing blocks

The following are executable constructs that contain blocks and may be used to control the execution sequence:

(1) IF Construct

(2) CASE Construct

(3) DO Construct

There is also a nonblock form of the DO construct.

A **block** is a sequence of executable constructs that is treated as a unit.

R801 *block* **is** [*execution-part-construct*] ...

Executable constructs may be used to control which blocks of a program are executed or how many times a block is executed. Blocks are always bounded by statements that are particular to the construct in which they are embedded; however, in some forms of the DO construct, a sequence of executable constructs without a terminating boundary statement shall obey all other rules governing blocks (8.1.1).

NOTE 8.1

A block need not contain any executable constructs. Execution of such a block has no effect.

Any of these constructs may be named. If a construct is named, the name shall be the first lexical token of the first statement of the construct and the last lexical token of the construct. In fixed source form, the name preceding the construct shall be placed after character position 6.

A statement **belongs** to the innermost construct in which it appears unless it contains a construct name, in which case it belongs to the named construct.

NOTE 8.2

An example of a construct containing a block is:

```
IF (A > 0.0) THEN
   B = SQRT (A)   ! These two statements
   C = LOG (A)    ! form a block.
END IF
```

8.1.1 Rules governing blocks

8.1.1.1 Executable constructs in blocks

If a block contains an executable construct, the executable construct shall be entirely within the block.

8.1.1.2 Control flow in blocks

Transfer of control to the interior of a block from outside the block is prohibited. Transfers within a block and transfers from the interior of a block to outside the block may occur.

NOTE 8.3

> For example, if a statement inside the block has a statement label, a GO TO statement using that label is only allowed to appear in the same block.

Subroutine and function references (12.4.2, 12.4.3) may appear in a block.

8.1.1.3 Execution of a block

Execution of a block begins with the execution of the first executable construct in the block. Unless there is a transfer of control out of the block, the execution of the block is completed when the last executable construct in the sequence is executed. The action that takes place at the terminal boundary depends on the particular construct and on the block within that construct. It is usually a transfer of control.

8.1.2 IF construct

The **IF construct** selects for execution no more than one of its constituent blocks. The **IF statement** controls the execution of a single statement (8.1.2.4).

8.1.2.1 Form of the IF construct

R802	*if-construct*	**is**	*if-then-stmt*
			    block
			  [*else-if-stmt*
			    block] ...
			  [*else-stmt*
			    block]
			  end-if-stmt

R803	*if-then-stmt*	**is**	[*if-construct-name* :] IF (*scalar-logical-expr*) THEN
R804	*else-if-stmt*	**is**	ELSE IF (*scalar-logical-expr*) THEN [*if-construct-name*]
R805	*else-stmt*	**is**	ELSE [*if-construct-name*]
R806	*end-if-stmt*	**is**	END IF [*if-construct-name*]

Constraint: If the *if-then-stmt* of an *if-construct* is identified by an *if-construct-name*, the corresponding *end-if-stmt* shall specify the same *if-construct-name*. If the *if-then-stmt* of an *if-construct* is not identified by an *if-construct-name*, the corresponding *end-if-stmt* shall not specify an *if-construct-name*. If an *else-if-stmt* or *else-stmt* is identified by an *if-construct-name*, the corresponding *if-then-stmt* shall specify the same *if-construct-name*.

8.1.2.2 Execution of an IF construct

At most one of the blocks in the IF construct is executed. If there is an ELSE statement in the construct, exactly one of the blocks in the construct will be executed. The scalar logical expressions are evaluated in the order of their appearance in the construct until a true value is found or an ELSE statement or END IF statement is encountered. If a true value or an ELSE statement is found, the block immediately following is executed and this completes the execution of the construct. The scalar logical expressions in any remaining ELSE IF statements of the IF construct are not evaluated. If none of the evaluated expressions is true and there is no ELSE statement, the execution of the construct is completed without the execution of any block within the construct.

An ELSE IF statement or an ELSE statement shall not be a branch target statement. It is permissible to branch to an END IF statement only from within the IF construct. Execution of an END IF statement has no effect.

8.1.2.3 Examples of IF constructs

NOTE 8.4

```
IF (CVAR .EQ. 'RESET') THEN
   I = 0; J = 0; K = 0
END IF

PROOF_DONE: IF (PROP) THEN
   WRITE (3, '("QED")')
   STOP
ELSE
   PROP = NEXTPROP
END IF PROOF_DONE

IF (A .GT. 0) THEN
   B = C/A
   IF (B .GT. 0) THEN
      D = 1.0
   END IF
ELSE IF (C .GT. 0) THEN
   B = A/C
   D = -1.0
ELSE
   B = ABS (MAX (A, C))
   D = 0
END IF
```

8.1.2.4 IF statement

The IF statement controls a single action statement (R216).

R807 *if-stmt* **is** IF (*scalar-logical-expr*) *action-stmt*

Constraint: The *action-stmt* in the *if-stmt* shall not be an *if-stmt*, *end-program-stmt*, *end-function-stmt*, or *end-subroutine-stmt*.

Execution of an IF statement causes evaluation of the scalar logical expression. If the value of the expression is true, the action statement is executed. If the value is false, the action statement is not executed and execution continues as though a CONTINUE statement (8.3) were executed.

The execution of a function reference in the scalar logical expression may affect entities in the action statement.

NOTE 8.5

An example of an IF statement is:

```
IF (A > 0.0) A = LOG (A)
```

8.1.3 CASE construct

The **CASE construct** selects for execution at most one of its constituent blocks.

8.1.3.1 Form of the CASE construct

R808 *case-construct* **is** *select-case-stmt*
    [*case-stmt*
        block] ...
    end-select-stmt

R809 *select-case-stmt* **is** [*case-construct-name* :] SELECT CASE (*case-expr*)

R810 *case-stmt* **is** CASE *case-selector* [*case-construct-name*]

R811 *end-select-stmt* **is** END SELECT [*case-construct-name*]

Constraint: If the *select-case-stmt* of a *case-construct* is identified by a *case-construct-name*, the corresponding *end-select-stmt* shall specify the same *case-construct-name*. If the *select-case-stmt* of a *case-construct* is not identified by a *case-construct-name*, the corresponding *end-select-stmt* shall not specify a *case-construct-name*. If a *case-stmt* is identified by a *case-construct-name*, the corresponding *select-case-stmt* shall specify the same *case-construct-name*.

R812 *case-expr* **is** *scalar-int-expr*
or *scalar-char-expr*
or *scalar-logical-expr*

R813 *case-selector* **is** (*case-value-range-list*)
or DEFAULT

Constraint: No more than one of the selectors of one of the CASE statements shall be DEFAULT.

R814 *case-value-range* **is** *case-value*
or *case-value* :
or : *case-value*
or *case-value* : *case-value*

R815 *case-value* **is** *scalar-int-initialization-expr*
or *scalar-char-initialization-expr*
or *scalar-logical-initialization-expr*

Constraint: For a given *case-construct*, each *case-value* shall be of the same type as *case-expr*. For character type, length differences are allowed, but the kind type parameters shall be the same.

Constraint: A *case-value-range* using a colon shall not be used if *case-expr* is of type logical.

Constraint: For a given *case-construct*, the *case-value-range*s shall not overlap; that is, there shall be no possible value of the *case-expr* that matches more than one *case-value-range*.

8.1.3.2 Execution of a CASE construct

The execution of the SELECT CASE statement causes the case expression to be evaluated. The resulting value is called the **case index**. For a case value range list, a match occurs if the case index matches any of the case value ranges in the list. For a case index with a value of c, a match is determined as follows:

(1) If the case value range contains a single value v without a colon, a match occurs for data type logical if the expression c .EQV. v is true, and a match occurs for data type integer or character if the expression c .EQ. v is true.

(2) If the case value range is of the form *low* : *high*, a match occurs if the expression *low* .LE. c .AND. c .LE. *high* is true.

(3) If the case value range is of the form *low* :, a match occurs if the expression *low* .LE. c is true.

(4) If the case value range is of the form : *high*, a match occurs if the expression c .LE. *high* is true.

(5) If no other selector matches and a DEFAULT selector is present, it matches the case index.

(6) If no other selector matches and the DEFAULT selector is absent, there is no match.

The block following the CASE statement containing the matching selector, if any, is executed. This completes execution of the construct.

At most one of the blocks of a CASE construct is executed.

A CASE statement shall not be a branch target statement. It is permissible to branch to an END SELECT statement only from within the CASE construct.

8.1.3.3 Examples of CASE constructs

NOTE 8.6

An integer signum function:

```
INTEGER FUNCTION SIGNUM (N)
SELECT CASE (N)
CASE (:-1)
   SIGNUM = -1
CASE (0)
   SIGNUM = 0
CASE (1:)
   SIGNUM = 1
END SELECT
END
```

NOTE 8.7

A code fragment to check for balanced parentheses:

```
CHARACTER (80) :: LINE
   ...
LEVEL=0
DO I = 1, 80
   CHECK_PARENS: SELECT CASE (LINE (I:I))
   CASE ('(')
      LEVEL = LEVEL + 1
   CASE (')')
      LEVEL = LEVEL - 1
      IF (LEVEL .LT. 0) THEN
         PRINT *, 'UNEXPECTED RIGHT PARENTHESIS'
         EXIT
      END IF
   CASE DEFAULT
      ! Ignore all other characters
   END SELECT CHECK_PARENS
END DO
IF (LEVEL .GT. 0) THEN
   PRINT *, 'MISSING RIGHT PARENTHESIS'
END IF
```

NOTE 8.8

The following three fragments are equivalent:

```
IF (SILLY .EQ. 1) THEN
   CALL THIS
ELSE
   CALL THAT
END IF
```

```
SELECT CASE (SILLY .EQ. 1)
CASE (.TRUE.)
   CALL THIS
CASE (.FALSE.)
   CALL THAT
END SELECT
```